



INTERNATIONAL JOURNAL OF CREATIVE RESEARCH THOUGHTS (IJCRT)

An International Open Access, Peer-reviewed, Refereed Journal

Aahar: Image To Recipe Generation

¹Dr. Reshma Totare, ²Vaibhavi Pawar, ³Mrunal Kshirsagar, ⁴Yash Satbhayya, ⁵Rutuja Ilag

¹Professor, ²Student, ³Student, ⁴Student, ⁵Student

¹Information Technology,

¹AISSMS Institute of Information Technology, Pune, India

Abstract: — For most individuals, cooking is a daily ritual. However, the same query arises again and time again: "What are we going to cook today?" Often, people get into a situation where they want to bake, cook or try something delicious, but lack the ingredients at home. Many times, people see an image of a delicious looking dish, but they don't know it's recipe. To address these challenges, this paper offers a summary of Machine Learning strategies that aim to generate recipes using only a list of desired ingredients as input, or even create them from scratch, in order to respond to that inquiry! Providing a user-friendly interface, nutrition, proteins, fats, carbohydrates value & a YouTube video link for easy understanding This project aims to alert the user to different dishes that can be cooked from the available ingredient sets, or to an input image entered by the user.

Index Terms - Cooking, Natural Language Processing, Recipe Creation and Machine Learning.

I. INTRODUCTION

Cooking is a vital chore because food is necessary for human survival. Even while it seems straightforward, it's actually quite complex because other components are incorporated in accordance with suit each person's specific requirements with relation to diet, calorie intake, taste, and even lifestyle decisions like becoming a vegetarian. And it becomes even more difficult when we consider that creating a cuisine that is actually tasty calls for a certain set of abilities. These days, cooking is more than just a basic necessity. While some see it as merely a pastime, others see it as a lucrative career, particularly the rise due social media , Food needs to taste amazing. In addition, it needs to be current with respect to the newest developments in terms of flavors, materials, and numerous other aspects. It has gotten so complicated that an entire new area called "Food Computing" has emerged to study every facet of it, with machine learning playing a major role. Early attempts to use artificial intelligence date back to 1986 with CHEF, which attempted to create new recipes for the Szechuan cuisine based on preexisting ones. cuisine. That has been a constantly changing process up to this point, moving from straightforward pattern matching to mine huge data using IBM Watson Chef and Deep Neural Networks.

There are many different kinds of challenges as well, ranging from picture recognition—which involves trying to reconstructing recipes or determining the nutrients of a dish from photographs – to similarly difficult text generation problems involving either ingredients alone or even entire recipes. The latter duties as well as advice on how to create new recipes based on the needs of users - whether according to generating wholly new ones or by modifying already-existing ones—will be the main focus of the proposed system. We will first go over a review of each method and a few frequently used datasets before having a talk about the unresolved problems in the field. The image corresponding to a meal is provided to estimate its nutritional value, which is important for many health applications.

II. LITERATURE SURVEY

Even while recipe creation and suggestion systems have advanced significantly, there are still some significant problems that need to be resolved and no one solution that is totally dependable.

A. Preserving the comparisons

The majority of recommendations rely on modifying recipes to achieve their desired outcomes, frequently with a direct substitution of components. Though it could sound like a good concept, the new component might have quite different qualities (such as texture, acidity, etc.), making the recipe implausible. When there are additional restrictions, such as dietary requirements where the caloric amount of the items matters, this problem gets much worse. Depending on nutritional data, some approaches try to address this issue by changing the quantity in addition to the item itself. However, a more "holistic" strategy that modifies the entire ingredient list rather than just some of the ingredients may be needed.

B. Variations in culture and component combinations

Sometimes the components work poorly together either because of their distinct flavor profiles or because they are just too similar. or simply because the flavor is surprising. For example, a western culture may find an Asian recipe somewhat strange, and vice versa. In certain situations, the consumer may even require that "surprise," but generally speaking, they anticipate a dish that tastes familiar. Even if there are situations where this problem cannot be fixed, it may be beneficial to filter the input recipes based on client or user preferences, whether they come from a case study or model training materials.

C. Chocolatier recipes

Occasionally, ingredient lists or cooking instructions may not make sense; this is frequently the case when the result is a novel recipe, not merely a modification, derived from a generative model. For example, it could be for an odd mix of ingredients or a cooking procedure that is just impossible to complete, such as "cut the water in pieces." In other tasks, such as automatic translation, where the user can actually understand the content based on the overall context, this problem may not be so critical as it relates to natural language processing and text generation in general, but in this case it is critical because the output recipe cannot be to perform.

clusters facilitate the extraction of meaningful insights from data, enhancing decision-making processes. Despite its simplicity, K-Means remains a robust and widely used clustering algorithm, making it an indispensable tool in data analysis and pattern recognition tasks.

III. RELATED WORK

Other attempts have been made to discuss advancements in the subject of cooking and recipes, but they primarily concentrate on different kinds of jobs or take a broader perspective. Burca released a synopsis of instances that combine machine learning techniques with conventional case-based reasoning, with recipe generation playing a minor role. An overview of food suggestion techniques was compiled by Trattner. On the other side, Min produced an evaluation that focused on the food computer "industry" as a whole rather than any particular subtasks.

This paper provides an overview of the concepts that had been proposed in the past ten years to address the issue of recipe production, including complete recipes that include ingredients and instructions, guidelines, or portions of them.

Our goal is to inform the user of the several recipes that can be prepared using the set of components that are readily available or an image that they have provided.

As a result, such systems are never appropriate in the actual world. Using a neural network, we have created a model for recipe generation. The project is being developed using Flask, JavaScript, React, CSS, and Python.

A website that uses machine learning techniques and is dynamic. Search possibilities include:

- Ingredients search;
- Food image search
- Look up by cuisine

Results: independently created recipe

This system does not function as a recommender; rather, it generates recipes!

An extra function that allows users to share posts with content connected to food

Algorithm & Approach

1. Scrap Dataset from given websites:

1. All Recipes
2. Epicurious
3. Food Network

2. Dataset Preprocessing:

1. Making the dictionary into a string and removing any unfinished recipes.
2. Insert stop words following the ingredients, instructions, and recipe title.
3. Reducing the length of the recipes by eliminating those that are too lengthy and adding a unique touch to the smaller ones. At last departed with 100212 recipes.

3. Final Training

For the final training, we transformed the input dataset into a Tensorflow dataset after vectorizing it into numbers using character level runs.

After that, we divided the dataset into 64-batch batches and then began the training.

We've used many Deep learning techniques:

- a. Adam, rmsprop, and SGD (Stochastic Gradient Descent) are the optimizers.
- b. Learning rate: fluctuating between 0.001 and 0.005
- c. Sparse_categorical_crossentropy and categorical_crossentropy as the loss functions

With the rmsprop Optimizer, sparse_categorical_crossentropy as the loss function, and 0.0005 as the learning rate, we were able to successfully attain a maximum accuracy of 93.20%.

Requirements for Modeling Knowledge :

Understanding of Web Development: This was necessary in order to create the recipe creation and registration processes. The team has experience with web development and has used Flask, a Python framework, for server-side scripting needs, and sqlite as the database. Recipe bowl uses React, JavaScript, CSS, and AJAX for the front-end. Deep learning knowledge was necessary because the application called for building a model that could assist in generating recipes. Our group was familiar with neural networks, and we especially used CNN's (convolutional neural networks) and RNNs (recurrent neural networks) in our application.

Understanding UML Diagrams: Understanding UML diagrams was necessary to generate the various model kinds.

Creating the Architecture Model:

- a) Server: The system needs servers to host databases, which are used for querying, as well as to process applications. The team has employed its local machines for development.
- B) Web hosting: In order to enable 24/7 access to the application and databases, they must be hosted online. The group has hosted apps on the localhost for development purposes.
- C) Ides: Specific ideas and tools are employed for each of the different technologies that are being used.

The group has made use of:

- I. Atom and Sublime Text for Web Development.
- II. Jupyter Notebook for Python Script Development


Dataset analysis

The source of this dataset is the UCI Machine Learning Repository. It includes 14 properties and 1500 rows. The characteristics include both simple ones like resting blood pressure and type of chest pain and more sophisticated ones like age, gender, and blood pressure. After that, the dataset was scaled to a range of 0 to 1 using Min Max scaling.

Three websites were used to obtain datasets through scraping:

1. Epicurious
2. All recipe
3. Food Network

The total number of raw instances is 125164. The size of the dataset after incomplete recipes are removed is 122938. The size of the dataset after very large recipes are filtered out and its length is fixed is 100212.



IV. METHODOLOGY

The goal is to develop an application that will let a user discover different recipes using the items they already have in their kitchen. The actions that must be taken are:

1. To investigate different linked datasets and carry out preprocessing on the data to extract the required attributes.
2. To train a model to determine the best matched recipes for a given set of ingredients using machine learning or deep learning methods.
3. To categorize and calculate the calorie content of any given dish from an input photograph.

Below is the explanation of the system architecture as shown in figure “2” and “3”




figure 2: fetching recipes.




figure 3: finding caloric values of recipes from images

A. Choosing the Right Cooking Literature

Using the search terms "chef ,recipe or cocktail) and "machine learning or deep learning or (NLP) Natural Language Processing" one can start looking for potential publications at Google Scholar and Scopus, with an emphasis on the last ten years or so. Following After removing a few early choices on the development of recipe creation, the collection was branched out to include their citations and references. The Conference proceedings are another excellent source of information because many of the systems discussed in the relevant section that are created for the Computer Cooking Contest, which compares results of the CBR system on cooking as an event that was part of the annual international conference on CBR 1.

B. The "Classic" method: Case - Based Reasoning (CBR) was the process of modifying previously known information to address a novel situation. Systems with this kind of capability are built around a <https://iccb21.org/> Case Base, which in this case a collection or database of recipes. The Case Base searches for data depending on the users or client requirements, that are typically expressed in Natural Language. In the event that no matches are discovered, the system tries to provide a fresh recommendation by switching out components and integrating to its Domain Knowledge (DK) - typically the tree that links to the nutrition, ingredients, flavors, or meal kinds or "matching the algorithm," as it is commonly known. The collection refers individual representations can be Conversational (that stored as sequence of questions and answers), Textual (which is stored as free text), or Structured (entities-classes).

As demonstrated in Figure“4”, Table builds a hierarchical tree with the recipe as it's base, ingredients connected to associated classes (such as those pertaining to cuisine, diet, ingredient type, etc.), and a price for every tree edge. Then, if modification is needed, it is either done by utilizing the tree in its direct combination with or without certain rules, or by making use of the nutritional data for each ingredient as an extra variable. To enhance the knowledge acquisition process, a publicly accessible wiki was created under the name WikiTaaable in addition to the core system.




figure 4: a hierarchical tree from.

Java was used to construct JaDaCook [10], which used a simple K-Nearest Neighbors method. The needed ingredients are extracted from the input, and the case base recipes are rated to a normalized of [0,1] range based on whether ingredients are specified in each of their titles or directions, and then chooses the ones that rank highest. Subsequent versions, 2.0 [11] and web [12], were released, with the interface and ingredient and recipe database receiving more enhancements than the main algorithm.

The technology uses crawling data from cooking community websites or substitutes missing items with the highest similarity score when adapting a recipe.

PHP was also used to construct the web-based system cooking CAKE. Recipes and ingredients are generalized in some classes to compute similarity, producing a tree, similar to other CBR frameworks. The individual nodes score—which is determined by taking into account each node's depth and the height of the tree for each ingredient—is the foundation for the similarity score. When necessary, a Naive Bayes classifier is employed to categorize the recipes and the ingredients according to the type of food, meal and cuisine. Its later iteration included the use of workflows, POQL, a language designed to give an organized the representation for Inquiries of case-based and process-oriented reasoning tasks, trying to modify not just the recipe components but also the workflow task as a whole or the subtasks. A workflow example of this type is shown in Figure “5”




figure 5: a workflow of cooking cake

In reality, Colibri Cook compares the input ingredients with those in the Case Base recipes in an effort to provide recipes that match, and then uses WEKA [20] to categorize when a culinary or diet limitation is present. is chosen.

C. Using a Deep Neural Network as the "Modern" method.

Text generation is the primary job involved in creating new recipes. It would therefore be reasonable to anticipate the use of specific architecture types: models of generation such as the Variational Autoencoder (seen in Fig. 3 in its most basic form), Recurrent Neural Networks(RNN), and Long Short-Term Memory Banks (LSTMs) that are able to preserve the context for the text being generated and even the more modern Transformers that are excellent at a variety of NLP tasks. While the other generative models such as GANs, that are employed in related tasks, that were left out since the goal at hand is producing ingredient lists or real cooking instructions, whereas these models are mostly utilized to produce food images from recipes. Several of the answers in this area just offer a portion of the recipe, that is, only the ingredients that are with or without necessary measurements or proportion and provide only directions for cooking).

In order to translate to the input ingredients into recipe, Bostan approaches recipe generation as a translation task. Following the creation of the word embedded of the ingredients that run through two LSTMs in a sequence to sequence architecture to generate the cooking steps needed for the intended recipe.




figure 6: a autoencoder architecture used for generative tasks.

Using a sequence to sequence model and as an attention to the mechanism, a different related method or process aims to create a recipe from a list of ingredients. It has an encoder that creates a representation for the input recipe from a sequence of ingredient embeddings, and a decoder transforms it into a set of cooking the dish with instructions.

Ingredients:

flour, sugar, bananas, eggs, chocolate chips, baking soda, vanilla, and butter.

Instructions:

- 1) Set aside a 9 x 5 x 3-inch loaf pan.
- 2) grease and flour it; and
- 3) beat the butter as well as sugar together until they are fluffy and light.
- 4) Gradually add eggs, beating thoroughly after each addition.
- 5) Add the mashed bananas and vanilla.
- 6) Mix the flour, baking soda, salt, and chocolate chips in another basin.
- 7) Stir the flour mixture just until incorporated after adding it to the creamed mixture.
- 8) Transfer to a Loaf pan.
9. Bake for sixty - seventy minutes, or until wooden pick inserted in the middle comes out as clean.
- 10) After 10 minutes of cooling in the pan, remove and let it cool fully on a wire rack or available material.

v. RESULTS

We used Teamviewer and Docker to train and test our model on DGX GPU. We attempted to retrieve the model using Adam, rmsprop, and SGD (Stochastic Gradient Descent) as our three optimizers. In addition, we adjusted the learning rate and the number of steps each epoch to do hyperparameter tweaking. Ultimately, we were able to attain a 93.20% accuracy rate with a 0.0005 learning rate with rmsprop as the optimizer.

The trained neural network has the following structure:




figure 7: trained neural network


We've used many Deep learning techniques:

1. Adam, rmsprop, and SGD (Stochastic Gradient Descent) are the optimizers.
2. The range of learning rates is 0.005 to 0.001.
3. Sparse_categorical_crossentropy and categorical_crossentropy are the loss functions.

With the rmsprop Optimizer, sparse_categorical_crossentropy as the loss function, and 0.0005 as the learning rate, we were able to successfully attain a maximum accuracy of 93.20%.

This study presents a user-friendly platform designed for converting food images into detailed recipes, emphasizing a streamlined interface and visually appealing design upon site entry.. The results of our project showcase a comprehensive journey through various stages of user interaction and system functionalities. Figure “7” illustrates the user login process, ensuring secure access. Following this, Figure “8” shows the features allowing users to categorize their needs. Subsequently, figure “9” depicts the friendly user interface. Additionally, Figures “10” and “11” provides the detailed recipe with instructions and

YouTube link. Figure “12” ensuring accessibility to a wider audience by allowing them to save the favorite recipes, dishes or post. These results collectively demonstrate the robustness and efficacy of our Aahar system.



The image shows a user interface for login and registration. On the left is a blue vertical bar with the word "Login" in white. To its right is a white card titled "Register". The card features an illustration of a person at a computer. Below the illustration are four input fields: "Username" (placeholder: username), "Email" (placeholder: email), "Password" (placeholder: password), and "Confirm Password" (placeholder: password). A "Register" button is at the bottom of the card.

figure 7:user login.



figure 8:features.

figure 9: user interface.




figure 10: recipe by ingredients

Recipes



figure 11: detailed recipe




figure 12: favorite recipes

VI. FUTURE SCOPE

The Aaahar that is Image to recipe generator as well as Ingredients to Recipe generator sometime may produces irrelevant output due to constraint on dataset size. Expanding our dataset and improving the text generation model. The Ingredients-to-recipe model can be further extended to overcome the issue. A Post's feed can be added to the website where people can add their recipes in the form of posts and may implement the discussion forum for question and answers among the users.

1. Obtaining entry to the MIT dataset and refining the Ingredients-to-Recipe generator through training.
2. It is possible to enhance the Post's feed by suggesting posts according to the preferences of the users.
3. A forum for user Q&A discussions.
4. Direct chat contact between peers.

VII. CONCLUSION

The dynamic website AAHAR uses deep learning methods. Search possibilities include: Ingredients search; Image search for food; Cuisine search This system does not function as a recommender; rather, it generates recipes! An extra function that allows users to share posts including content connected to eating. We have created an online application that asks the user to enter ingredients, recipes, or images. The application then creates mouthwatering recipes for you. In conclusion it appears that both novice and expert cooks are constantly searching for the "ideal recipe." Cooking is the one of the topics that is currently in the boom and spotlight due to the rise of social media and everyone is attempting to develop inventive, delicious, healthful, and simple to prepare meals.

Using machine learning to the task can be beneficial in finding the appropriate recommendations among large databases, customizing them, or even creating innovative new mixtures of the constituents. Although the procedure isn't always going to produce the desired outcomes and can be rather funny at times, it can offer the background information and ideas that serve as the basis for the real solution. Even if Artificial Intelligence still seems long way from producing "robotic chef," employing concepts of deep learning could be done that moves that goal closer. NLP is now experiencing its "Golden Age" as a subset of that field, "age," and recipe generation, it is unclear what the next development will hold.

REFERENCES

- [1] K. J. Hammond, "Chef: A model of case-based planning." in AAAI, vol. 86, 1986, pp. 267–271.
- [2] Fotios S. Konstantakopoulos, Eleni I. Georga and Dimitrios I. Fotiadis "Review of image-based machine learning for food recognition and volume estimation" IEEE 2023 Biomedical Engineering Reviews DOI: 10.1109/RBME.2023.32831
- [3] 2. Bin Zhu, Chong-Wah Ngo, and Wing-Kwong Chan "Learning from web map-image pairs for food information: Issues, principles, and performance," 2022 IEEE Transactions on ON Multimedia, VOL. 243.
- [4] 3. He Lili, Cai Zhiwei, "Food recognition model based on deep learning and listening mechanism" 2022 IEEE Access 8th International Conference on Big Data Computing and Communications 10.1109/BigCom57025.20242.00
- [5] 4. Frank Po Wen Lo, Yingnan Sun, Jianing Qiu and Benny Lo "Image-based volume estimation for food classification and nutritional assessment: a review," 2020 IEEE Journal of Biomedical and Health Informatics, VOL. 24. No. 7 DOI: 10.1109/JBHI.2020.2987943
- [6] L. R. Varshney, F. Pinel, K. R. Varshney, D. Bhattacharjya, A. Schorgendorfer, and Y.-M. Chee, "A big data approach to computational creativity: The curious case of chef watson," IBM Journal of Research and Development, vol. 63, no. 1, pp. 7–1, 2019.
- [7] D. Burca, M. Schuller, and J. Zlabinger, "Case-based reasoning and machine learning," 2018.
- [8] C. Trattner and D. Elswiler, "Food recommender systems: important contributions, challenges and future research directions," arXiv preprint arXiv:1711.02760, 2017.
- [9] W. Min, S. Jiang, L. Liu, Y. Rui, and R. Jain, "A survey on food computing," ACM Computing Surveys (CSUR), vol. 52, no. 5, pp. 1–36, 2019.
- [10] J. L. Kolodner, "An introduction to case-based reasoning," Artificial intelligence review, vol. 6, no. 1, pp. 3–34, 1992.

- [11] R. Bergmann, K.-D. Althoff, S. Breen, M. Goker, M. Manago, " R. Traphoner, and S. Wess, " Developing industrial case-based reasoning applications: The INRECA methodology. Springer Science & Business Media, 2003.
- [12] A. Cordier, V. Dufour-Lussier, J. Lieber, E. Nauer, F. Badra, J. Cojan, E. Gaillard, L. Infante-Blanco, P. Molli, A. Napoli et al., "Taaable: a case-based system for personalized cooking," in Successful Case-based Reasoning Applications-2. Springer, 2014, pp. 121–162.
- [13] F. Badra, J. Cojan, A. Cordier, J. Lieber, T. Meilender, A. Mille, P. Molli, E. Nauer, A. Napoli, H. Skaf-Molli et al., "Knowledge acquisition and discovery for the textual case-based cooking system wikitaable," in 8th International Conference on Case-Based Reasoning-ICCBR 2009, Workshop Proceedings, 2009, pp. 249–258.
- [14] P. J. Herrera, P. Iglesias, D. Romero, I. Rubio, and B. D'íaz-Agudo, "Jadacook: Java application developed and cooked over ontological knowledge." in ECCBR Workshops, 2008, pp. 209–218.
- [15] P. J. Herrera, P. Iglesias, A. M. G. Sanchez, and B. D'íaz-Agudo, "Jadacook 2: Cooking over ontological knowledge," in 8th International Conference on Case-Based Reasoning (ICCBR-09), 2009, pp. 279–288.
- [16] M. Ballesteros, R. Martín, and B. Díaz-Agudo, "Jadaweb: A cbr system for cooking recipes," in Workshop Proceedings, 2010, p. 179.
- [17] A. Hanft, R. Newo, K. Bach, N. Ihle, and K.-D. Althoff, "Cookiis—a successful recipe advisor and menu creator," in Successful Case-based Reasoning Applications-I. Springer, 2010, pp. 187–222.
- [18] C. Fuchs, C. Gimmmler, S. Gunther, L. Holthof, and R. Bergmann, " "Cooking cake," in ICCBR, vol. 9, 2009, pp. 259–268.
- [19] G. Muller and R. Bergmann, "Cookingcake: A framework for the " adaptation of cooking recipes represented as workflows." in ICCBR (Workshops), 2015, pp. 221–232

